

55 inch Double-sided outdoor floor signage

SKU:

EAN:



FEATURES

- High-definition and high-brightness display
Automatic light sensor, adjusts screen brightness according to ambient light, saves energy and reduces light pollution
- Industrial Protection Technology
The integrated chassis and constant temperature system meet the IP55 full outdoor equipment standard.
- Diverse Advertising Styles
Support pictures, video, text and other mainstream audio and video formats
- Smart split screen
Multiple split screen modes, pictures and videos can be played simultaneously



SPECIFICATION

	Air Cooling	Air conditioner
Size	55 inch LCD	55 inch LCD
Display area	1209*680mm	1209*680mm
Touch style	no Touch	no Touch
Ratio	16:09	16:09
Resolution	1920*1080	1920*1080
Brightness	3000cd/m2	3000cd/m2
Contrast	4000:1	4000:1
Angle	178°horizontal /178°vertical	178°horizontal /178°vertical
CPU	RK 3568	RK 3568
Ram	4GB	4GB
Storage	32G	32G
Port	USB*2 RJ45*1	USB*2 RJ45*1
Protective level	IP 55	IP 65
Weight	100KG	100KG
Install	floor standing	floor standing
Glass	6mm Tempered explosion-proof glass	6mm Tempered explosion-proof glass
Video port	VGA 、HDMI	VGA 、HDMI
Audio port	I/O input and output	I/O input and output
Brightness control	A utomatic photosensitive	A utomatic photosensitive
Temperature control	Smart fan automatic temperature sensing	Smart fan automatic temperature sensing
Working temperature	-20°C to +40°C	-20°C to +40°C
Working humidity	5% to 90%	5% to 90%

Source	220V	220V
Power	400W	1200W
Sheet sheet metal shell	Sheet metal shell adopts 1.5mm SGCC galvanized steel sheet, the inner layer is coated with zinc-rich bottom powder, coated with DuPont outdoor plastic powder protection, the service life to ensure more than 10 years;	
Explosion-proof glass	6mm tempered glass, when the glass is damaged by external forces, the debris will become similar to honeycomb blunt angle broken small particles, not easy to cause serious harm to the human body. The impact strength of tempered glass is 3~5 times that of ordinary glass, and the bending strength is 3~5 times that of ordinary glass.	
Bright LCD screen	Outdoor special bright LCD display screen, LED straight down backlight, visible in sunlight Screen resolution HD 1920 * 1080; Automatic light sensing probe, adjust the screen brightness according to the environmental light, energy saving and electricity saving, reduce light pollution;	
Play the system	Android network information release system; Support pictures, video, text and other mainstream audio and video formats; Support for wired / wireless WiFi network transmission; Support pictures, video, text and other mainstream audio and video formats; Support for wired / wireless WiFi network transmission; Support stand-alone plug card playback;	
Electric control system	Leakage protection switch, leakage protection, overvoltage protection; Micro computer timing switch, time-timing control machine start and stop; Lightning protection device, lightning protection level C, prevent instantaneous induction lightning; Taiwan Mingwei industrial grade power supply, stable and reliable power supply;	
Radiation system	Intelligent fan integrated temperature control, meet the outdoor environment of -30~+50 degrees the display screen is not black, the machine works normally; Adopt the axial flow fan, supporting the fan speed control board, automatic temperature sensing, automatic adjustment of the fan speed, energy saving and power saving, prolong the service life of the fan; High efficiency multi-layer filtration system, isolate harmful dust into the machine interior, the protection level of the whole machine reaches IP65;	
Test macro	Spray and waterproof test; High and low temperature test; Solar radiation test; Whole machine aging test;	