

55 inch signage displays with touch



SKU:

EAN:

FEATURES

● Wall-Mounted LCD Advertising Display

Featuring HD resolution and a 178° wide viewing angle, this display supports continuous loop playback, includes built-in speakers, and runs on either Android or Windows operating systems. Its highly responsive multi-touch interface—powered by a sensitive 10-point PCAP touchscreen—delivers a precise and accurate touch experience. With multi-touch capabilities and a rapid 6ms response time, it allows for intuitive zooming in and out, ensuring every detail is showcased in full clarity.

● Versatile Display Options

Support for scrolling text, static company logos, dates, calendars, and time displays enables you to present your advertisements in a multitude of creative ways. The unit features automatic loop playback; simply insert a USB drive to automatically detect files and play advertising content. You can also customize playback schedules for seamless content transitions.

● Flawless HD Video Playback

Supports both horizontal and vertical screen orientations, maintaining consistent color and contrast from any viewing angle—ensuring you enjoy high-quality imagery even in indoor environments.

● Intelligent Split-Screen Functionality

Supports split-screen capabilities, allowing for the simultaneous display of audio, video, images, text, and other information combinations. With remote management capabilities, you can instantly publish content with a single click via mobile phone or computer, enabling unified management across different display zones and devices.



SPECIFICATION

Panel

Dimension	55 inch LCD screen
Touch style	IR 10 points touch
Resolution	Full HD 1920 x 1080
Screen scale/Display area	1209mm * 680.5 mm
Display color	16.7M
Visual angle	H: 178° V: 178°
Brightness	400-450 cd/m2
Contrast	1300:1
Response time	5ms
Screen Life(hrs)	> 50,000(hrs)

Configuration	
CPU	RK3566S
Memory	2G DDR3
Storage	32GB Normally, EMMC NAND chip
OSD language	Multi language support
System	Android 11.0
Network	
Ethernet	10M/100M
WiFi	802.11 b/g/n WiFi 5
Bluetooth	Support V2.1+EDR/BT v3.0/BT v3.0+HS/BT v4.0
Interface	
USB Port	USB 2.0
RJ45	10M/100M
TF Card	Push-push type TF socket, support at most 32GB TF card
HDMI	Input *1/Output*1
Multi-Media	
Video	Support MPEG-1, MPEG-2, MPEG-4, H.263, H.264, RV, etc. (max support 1080P)
Audio	Support MP4, WMA, AAC and so on
Picture	JPEG, PNG, BMP and so on
Power	
The input voltage	AC100-240v 50/60HZ
Standby power	≤1W, support low power standby mode
Other parameters	
Material	Metal case
Speaker	2×5W speakers (8Ω)
Color	Black Normally, OEM support
Installation	Wall mounted
Operating temperature/humidity	0℃~50℃/20% ~ 80%
Store temperature/humidity	-10℃~60℃/5--95%
Software	Free installation applications (maps, games, e-mail, self developing apps, etc.)
Attachment	
Power Cable	One
Warranty card	One
Qualification certificate	One
User's Manual	One
Screw and Key	One
Antenna	One