

# 55-inch vertical double-sided LCD indoor Kiosk



SKU:

EAN:

## FEATURES

### ● Remote control terminal

Operated by the free content management software with either local or remote access, standby, wake up, auto-restart, etc.

### ● Real-time remote monitoring

Remote monitoring and control using WiFi or ethernet cable connection, remote management available through built-in CMS system, without the need to manually visit the display.

### ● Timing control

The timer can be set for one day or different setting for each day, with multiple timings per day.

### ● Stand-alone play

Support U-disk import of media for single-player playback and auto-restart.

### ● Intelligent cleaning

The system supports an intelligent cleaning function. When the local memory is full, it automatically removes the earliest files.



## SPECIFICATION

	Configure	Parameter
TFT LCD	size	55 Inch
	Physical resolution	3840 * 2160
	Displays the size	679.4× 1208.75mm
	Show color	16.7M
	Visual Angle	H: 176° V: 176°
	luminance	400cd/m
	contrast ratio	4000:1
	response time	6ms
Source	input voltage	AC100-240v 50/60HZ
	Complete machine power consumption	≤105W
	Standby power	1W, which supports the low-power standby mode
Surface	material quality	Tempered glass + aluminum profile frame
	Appearance color	Black (customizable)
	way to install	vertical
Work environment	Operating temperature / humidity	0°C~50°C/20% ~ 80%
	Storage temperature / humidity	-10°C~60°C/5--95%
	Machine life	For 50,000 hours
	<b>Configure</b>	<b>Parameter</b>
	CPU	RK3288, Cortex-A17 architecture, frequency 1.8G (optional)

Internal storage	DDR3 2G
Built-in memory	EMMC FLASH 16GB
Decoding resolution	Top support is 3840 * 2160
Operating system	Android 9.0
Play mode	Support loop, timing slot and other playback modes
Communication network support	Support for 4G, Ethernet, support for WiFi, wireless peripheral extension 1080P, Bluetooth 4.0
Video play	Supported video encapsulation formats include WMV, MP4, AVI, TS, MPEG, FLV, RMVB, RM, etc
Picture format	Supporting BMP, JPEG, PNG, etc
The USB2.0 interface	2 USB HOST, 4 USB outlets
Ethernet	1,10M / 100M adaptive Ethernet
WIFI 、 BT	Built-in WIFI, BT4.0 (optional)
HDMI output	1, supporting 1080P output
Information release software	Single machine, LAN, wide area network
Audio and video output	An audio output
RTC, real-time clock	Support
Timed switch machine	Support
system upgrade	Support computer updates