

8" Active Monitor Speaker

SKU:

EAN:

FEATUES

- Enjoy the shocking sound effects of the cinema experience at home, precision-made speakers, high-power 26mm metal dome tweeter, high-strength alloy precision die-cast cabinet, the cabinet material is high-density aluminum alloy, which improves the response characteristics of the rear edge of the speaker, making the sound cleaner and clearer.
- Monitor recording studio, monitor real sound, 8-inch professional active 2.0 monitor speakers, using a newly developed 8-inch large dynamic woofer and 26mm metal dome tweeter, 130W per channel, built-in amplifier.
- Three-way frequency adjustment has frequency adjustment function, users can adjust high frequency/mid-frequency/low frequency according to different environments. Scope of application supports a variety of music players, mobile phones, tablets, desktop computers, etc. Excellent electro-acoustic active monitor speakers with good sound reproduction and stylish oval cabinet shape. Egg-shaped low-diffraction cabinet design with acoustic characteristics. The oval structure makes the sound quality reach extremely high purity.
- 8-inch woofer creates wonderful bass, 8-inch large-caliber woofer, long-stroke high-power design, restore the sound field. Bass and treble two-way design created by 26mm metal dome tweeter. Multi-dimensional high-damping rubber shockproof base, providing multi-point contact, the height of the cabinet can be adjusted at will to avoid sound distortion caused by additional vibration.



SPECIFICATION

System	Two-way Reverse Phase System
Unit	8" mid-low range ; 26mm metal tweeter
Frequency	35Hz-20kHz(+ 2.5dB, free space)
Distortion	55Hz-20kHz($\leq 1\%$;85dB/1m)
Filter type	Professional Active Electronic Crossover Filter
Rated power	130W RMS per channel
Active electronic crossover point	2.5kHz
Bass adjustment	+2/0/-2dB(200Hz)
Mid-range adjustment	0/-2/-4dB(500Hz)
Treble adjustment	+1/0/-1dB(10kHz)
LF cutoff frequency	35Hz/60Hz/80Hz
Signal-to-noise ratio	>94dB(unweighted)
Input sensitivity	350mv
Input impedance	12k Ω

Input peak	3000mV
Appearance	Paint,High-strength cast aluminum box
Dimension	294x283x415mm(LxWxH)
Net weight	13.2kg