SKU: 0200154 EAN:



## **FEATUES**

The Edis CO2 Smoke and Monitor is Dual channel vents, Real-time detection of carbon dioxide data changes, scientific ventilation design, ventilation and heat dissipation faster, the sensor work efficiently, Hanging design Multiangle view is not backlit, with 2 meters long data line, 24 hours detection data constant electricity. Real-time detection and fast measurement Carbon dioxide measurement range:0-5000PPM Resolution:1PPM. Combo CO2 and Smoke Alarm Detector Place of use home Classroom Office Gym Factory Greenhouse...



## **CO2 SMOKE AND MONITOR**

Material	Fire resistant ABS+LCD
Smoke sensor	photoeletric smoke sensor
CO2 sensor	NDIR CO2 sensor
Temperature measuring range	400-5000ppm±5%
Humidity measuring range	-20°C-60°C ±2%
Co2 and smoke alarm	5%-95% ±5%
Smoke sensitivity	85dB (1-3M)
Battery capacity	0.1% db/m-0.3% db/m
Resolution	1400mAh
Storage temperature	1 PPM
Power supply	-10 -60°C
Warm-up time	Chargeable battery and 2M long USB
Product size	<7 Seconds
Product weight	102mmx52mmx140mm
Customize	320g