

# ECT40 Video Controller

SKU: 0200140

EAN:



## FEATUES

- Multi-camera live production Large-scale summits, cultural performances, and sports events often require multi-camera shooting, and the L1 PLUS is equipped with 4-channel HDMI inputs, supporting up to 4K@60Hz. This means you can connect 4 signal sources at the same time to get different views, easily handling various multi-camera live productions.
- Multi-camera connection, the L1 PLUS is equipped with 4 HDMI, which is perfect for medium or large multi-camera live broadcasts. For medium-sized live broadcasts, you can use 2 or 3 cameras to capture close-ups or panoramas from different angles, and you can also connect a PC to play PPT; for large live broadcasts, you can use 3 or 4 cameras, and you can also connect a PC to play PPT or connect a PTZ controller.
- All pictures can be quickly switched through the T-bar and buttons. Supports PTZ control. In the same LAN, you can easily control the rotation of the PTZ camera through the joystick on the panel. Equipped with a 2-inch touch screen, you can preview the input picture, or connect to an external larger display through the HDMI output to get a larger preview picture and audio status. Connect to a computer through the USB 3.0 streaming interface, and you can live broadcast on your favorite platform.
- Suitable for weddings, church events, sports events, kitchens, and live concerts, etc. With its user-friendly interface and comfortable buttons, you can easily master its functions. For video creators or anyone who wants to simply and quickly produce broadcast-quality multi-camera programs from anywhere. You can live broadcast to YouTube/Facebook/Instagram or use Skype or ZOOM for innovative business presentations, easily control each screen with a PTZ camera, and save up to 8 scenes for fast switching. Plug and play, you don't need to be a video professional to get excellent results.



## SPECIFICATION

Screen	2" TFT Touch Screen
Input	4xHDMI-A(4K)
Output	1xHDMI-A(2K)
Audio	USB 3.0 *1 (Streaming) 3.5MM*2 Input 3.5MM*1 Output
Communication	LAN 1
Power	1x USB-C
Input Resolutions	HDMI SMPTE 720p@50/60 1080i@50/60 1080p@24/30/50/60 2160p@60 VESA 1024X768@60 1280X720@60 1280X768@60 1280X800@60 1280X1024@60 1360X768@60

1366x768@601440x900@60|1600x1200@60|1680x1050@60|1920X1080@60 1920X 1200@60

3840x2160@604096x2160@60

Output Resolutions	HDMI SMPTE 720p@50/601080p@24/25/30/50/60 VESA 1024X768@601280x720@50/601280X768@60 1280X1024@601360x768@60 1920x1080@24/25/30/50/60 USB 1024X768@601280x720@50/601280X768@601280X1024@60 1360x768@60 1920x1080@24/25/30/50/60
Supported Standards	HDMI 2.0 USB 3.0 H.265ITU-TH.265/ISO/EC 23008-2
Supported Protocol	PTZ WISCA
Video Formats	HDMI2.0 HDCP 2.2
Streaming Formats	ITU-T H.265 ISO/IEC 23008-2
Audio Formats	LPCM/2ch/24bit/16bit/48kHZ
Color Space	R G B
Video Sampling	4:4:4 YUV
Video Latency	<4 frames
Input Voltage	DC 12V/1.5A
Power	< 20W
working Temperature	0°C~60°C
Humidity	10%~85%
Unit Size	194mmx109.6mmx47.8mm
Unit Weight	468g
Screen	2" TFT Touch Screen
Input	4xHDMI-A(4K)
Output	1xHDMI-A(2K)
Audio	USB 3.0 *1 (Streaming) 3.5MM*2 Input 3.5MM*1 Output
Communication	LAN 1
Power	1x USB-C
Input Resolutions	HDMI SMPTE 720p@50/601080i@50/601080p@24/30/50/60 2160p@60 VESA 1024X768@601280X720@60 1280X768@60 1280X800@60 1280X1024@601360X768 1366x768@601440x900@60 1600x1200@601680x1050@601920X1080@60 1920X 1200@60 3840x2160@604096x2160@60
Output Resolutions	HDMI SMPTE 720p@50/601080p@24/25/30/50/60 VESA 1024X768@601280x720@50/601280X768@60 1280X1024@601360x768@60 1920x1080@24/25/30/50/60 USB 1024X768@601280x720@50/601280X768@601280X1024@60 1360x768@60 1920x1080@24/25/30/50/60
Supported Standards	HDMI 2.0 USB 3.0 H.265ITU-TH.265/ISO/EC 23008-2
Supported Protocol	PTZ WISCA