

ET49 11.6 All-in-one terminal

SKU: 0200149

FEATUES

The Edis ET49 11.6 All-in-one terminal is a 11.6 inch screen size Intel tablet PC, OS: Windows 10 Pro, CPU: Intel Apollo Lake Celeron J3355 Dual-Core, Touch panel: G + G, Multi-touch, LCD Display: 1920*1080(250ANSI), DDR: 4GB LPDDR4 EMMC64GB, Wireless: 5G&2.4GHz Wifi, Bluetooth: V4.0, BT4.0, RJ-45 GigE, USB2.0*2, USB3.0*2, RS232*3, RS485*1, HDMI, Speakers*2, etc. TF Card slot(up to 128GB), Feature: Wake up on Lan, Power on by Clock, Fanless design. Dimension: 283*177*39.4mm, Power adaptor: 12V,2A



SOFTWARE CONFIGURATION

Type	Details	Descriptions
Power on Function	By Power Button or Auto Power on	Optional
Wake up on Lan	Wake up on Lan by RJ45	Support
PXE	Preboot Execution Environment	Support
Operating System	Windows 10;Linux	Optional Test by end user

MAIN ACCESSORIES

Type	Details	Descriptions
Power adapter	DC 12V/2A	×1pc
User's Manual	User's Manual	×1pc

SYSTEM HARDWARE CONFIGURATION

Type	Details	Descriptions
------	---------	--------------

SYSTEM PHYSICAL CONFIGURATION

Type	Details	Descriptions
Product Form	Form Factor	11.6" mini Aio PC
	Dimensions Weight	283 x 177 x 73mm 1.25KG
LED	Screen Size	11.6" 1920x1080 (IPS + 250ANSI)
	Screen Resolution	
TP	Touch Module	G+G Multi-Touch
Battery	Recharge Li-ion battery	Optional

BUTTON SWITCH

Type	Details	Descriptions
Power	On/Off	×1pc
Volume	Down/UP	×1pc
CMOS Reset	Reset by Short Press	Optional

INTERFACE CONFIGURATION

Type	Details	Descriptions
------	---------	--------------

CPU	Type Speed	1.10GHz ~ 2.20GHz Intel HD Graphics 500	USB Interface	USB3.0 Host USB2.0 Host	×2pcs ×1pc
Memory	Capacity	4GB (LPDDR4)	Audio Jack	3.5mm headphone	×1pc
Storage	eMMC SSD (M.2; 22×42mm)	64GB Optional (Support Customized as MOQ order)	HDMI	HDMI 1.4 Video output through HDMI	×1pc
Speaker	Built-in	8Ω/1W	COM Port	DB9 (RS232) / (RS485)	×4pcs (RS232×3pcs + RS485×1pc)
Micphone	Built-in	Optional			
G-sensor	Built-in	Yes			

ENVIRONMENT

Temperature	OperationTemperature Storage Temperature	-10°C ~ 50°C (1080p or 4K local video display)-20°C ~-70°C (Restore to Operation Temperature 2hr before use)
Humidity	Operating Humidity Storage Humidity	35% ~ 80% relative humidity, Non-condensing 20% ~ 93% relative humidity, Non-condensing

CERTIFICATION

CE	CE	Optional
Other	Other	Optional

NETWORK CONNECTIONS

Type	Details	Descriptions
WIFI	WIFI Module: Intel AC3165	WIFI 802.11ac/b/g/n 5G&2.4G Dual-band
Bluetooth	BT Module: Intel AC3165	Bluetooth4.2
Ethernet Network	RJ-45	100/1000Mbps Gigabit Lan
4G LTE	M.2 4G module	Optional