

# Novastar VX600 controller

SKU: 0030015-600

EAN:



## FEATUES

The Edis Novastar VX600 controller is a 10-network port 2-in-1 video controller integrates video processing and control functions. It can be widely used in high-end leasing, stage control and engineering small spacing LED display fields. One machine multi-purpose performance super group, video control, Bypass, photoelectric conversion, three modes optional. Ten practical choice of road network. 10 gigabit network port output, with a load of up to 6.5 million pixels. The widest output width of a single device is 10240 pixels and the highest output width is 8192 pixels. High quality 4K 3 layers 4K×1K@60Hz HD input, 4K×1K point-to-point easy display, image infinite zoom, 4K 3 layers super multi-function.



## SPECIFICATIONS

|                                  |                 |  |
|----------------------------------|-----------------|--|
| Electrical specifications        | power interface | 100-240V~, 1.5A, 50/60Hz   |
|                                  | rated power     | 28W  |
| Work environment                 | Temperature     | -10°C ~ +45°C  |
|                                  | humidity        | 20%RH to 90%RH, non-condensing   |
| Storage environment              | Temperature     | -20°C ~ +70°C  |
|                                  | humidity        | 10%RH to 95%RH, non-condensing   |
| Physical specifications          | size            | 483.6mm×351.2mm×50.1mm   |
|                                  | net weight      | 4kg  |
| package                          | accessories     | Power cord, HDMI to DVI cable, USB cable, Network cable, HDMI Cable, Quick Guide, certificate, safety manual, letter to user |
|                                  | carton          |  |
|                                  | total weight    | 565.0mm ×175.0mm ×450.0mm<br>6.8kg   |
| Noise Level (Typical, 25°C/77°F) | 45dB (A)        |  |