

USB-C PD Power Adapter



SKU:

EAN:

FEATUES

- Intelligent MCU control. Ultra low internal resistance, MOS transistor, Schottky. The shell is made of double-sided aluminum sheet, which provides better heat dissipation effect. Beautiful and elegant, the shell is made of high temperature resistant and flame-retardant materials, and ultrasonic welding is used for safe and reliable use
- Adopting efficient, low loss, and environmentally friendly circuit design; Equipped with overvoltage protection and overload protection; Good anti-interference performance; Small DC ripple, low noise; Low operating temperature and long lifespan; Wide voltage input, suitable for universal standards; Good insulation performance and high dielectric strength; Made of ABS+PC material, with fireproof function, stable and environmentally friendly



SPECIFICATION

Input	AC 100V-240V 50-60Hz	AC 100V-240V 50-60Hz	AC 100V-240V 50-60Hz
OUTPUT	20.0V-3.25A 15V-3A 12V-3A 9V-2A 5V-2A	20.0V-4.5A 15V-3A 12V-3A 9V-2A 5V-2A	20.0V-5A 15V-3A 12V-3A 9V-2A 5V-2A
Watt	65W	90W	100W
DC PIN	USB TYPE C	USB TYPE C	USB TYPE C
DC Cable Length	1.5 Meters	1.5 Meters	1.8 Meters
Protection	OTP/OVP/SCP/OCP	OTP/OVP/SCP/OCP	OTP/OVP/SCP/OCP
Certificate	CE/CB/FCC/ROHS/BIS	CE/CB/FCC/ROHS/BIS	CE/CB/FCC/ROHS/BIS