

Ultra Thin 55 inch Double-sided outdoor floor signage



SKU:

EAN:

FEATURES

- It uses a high-brightness LCD screen specially designed for outdoor use, which is visible under strong light, with high-definition picture quality and screen resolution of 1920*1080. The intelligent light-sensing system can automatically adjust the screen brightness according to the environment, so that users can watch programs clearly/comfortably at different times to protect their eyes. Intelligent color calibration, automatic calibration of contrast colors or manual fine-tuning, presents a perfect picture.
- Playback mode: supports loop, timing, interstitial, split-screen partition playback, supports any combination of multimedia materials, and other playback modes. Video playback: supports WMV, AVI, FLV, RM, RMVB, MPEG, TS, MP4, VOD, MOV, MKV, MP3, AAC and other formats. Picture format: supports JPEG, PNG, GIF, BMP, etc. File format: supports TXT, PPT, WORD, ECELE, etc. Video output: supports LVDS format video output. Audio output: supports HDMI high-definition video output



SPECIFICATION

Size	55 inch Wide Temperature LCD
Display area	1209*680mm
Touch style	no Touch
Ratio	16:09
Resolution	1920*1080
Brightness	3000cd/m2
Contrast	4000:1
Angle	178°horizontal /178°vertical
CPU	RK 3568
Ram	4GB
Storage	32G
Port	USB*2 RJ45*1
Protective level	IP 66
Weight	100KG
Install	floor standing
Glass	6mm Tempered explosion-proof glass
Video port	VGA 、 HDMI
Audio port	I/O input and output
Brightness control	A utomatic photosensitive

Temperature control	Smart fan automatic temperature sensing
Working temperature	-30°C to +50°C
Working humidity	5% to 90%
Source	220V
Power	350W
Sheet sheet metal shell	<p>Sheet metal shell adopts 1.5mm SGCC galvanized steel sheet, the inner layer is coated with zinc-rich bottom powder, coated with DuPont outdoor plastic</p> <p>powder protection, the service life to ensure more than 10 years;</p>
Explosion-proof glass	<p>6mm tempered glass, when the glass is damaged by external forces, the debris will become similar to honeycomb blunt angle broken small particles, not easy</p> <p>to cause serious harm to the human body. The impact strength of tempered glass is 3~5 times that of ordinary glass, and the bending strength is 3~5 times that</p> <p>of ordinary glass.</p>
Bright LCD screen	<p>Outdoor special bright LCD display screen,</p> <p>LED straight down backlight, visible in sunlight</p> <p>Screen resolution HD 1920 * 1080;</p> <p>Automatic light sensing probe, adjust the screen brightness according to the environmental light,</p> <p>energy saving and electricity saving, reduce light pollution;</p>
Play the system	<p>Android network information release system; Support pictures, video, text and other mainstream audio and video formats; Support for wired / wireless WiFi</p> <p>network transmission;</p> <p>Support pictures, video, text and other mainstream audio and video formats;</p> <p>Support for wired / wireless WiFi network transmission;</p> <p>Support stand-alone plug card playback;</p>
Electric control system	<p>Leakage protection switch, leakage protection, overvoltage protection;</p> <p>Micro computer timing switch, time-timing control machine start and stop;</p> <p>Lightning protection device, lightning protection level C, prevent instantaneous induction lightning;</p> <p>Taiwan Mingwei industrial grade power supply, stable and reliable power supply;</p>
Radiation system	<p>Intelligent fan integrated temperature control, meet the outdoor environment of -30~+50 degrees the display screen is not black, the machine works normally;</p> <p>Adopt the axial flow fan, supporting the fan speed control board, automatic temperature sensing, automatic adjustment of the fan speed, energy saving and</p> <p>power saving, prolong the service life of the fan; High efficiency multi-layer filtration system, isolate harmful dust into the machine interior, the protection level of</p> <p>the whole machine reaches IP65;</p>
Test macro	<p>Spray and waterproof test; High and low temperature test;</p> <p>Solar radiation test; Whole machine aging test;</p>