

VHD-V60CL-N Spec

Main Features	<ul style="list-style-type: none"> ●Supports NDI HX, HX2 The camera can connect directly to a NDI® network, utilizing NDI-based video production workflows without additional configuration, reducing cost and set-up time. ●1080P Full HD Apply 1/2.8 inch, 2.07 million effective pixels high quality HD CMOS sensor, can reach maximum 1920 x 1080 high resolution and achieve quality image. ●Ultra-high Frame Rate The output frame rate up to 60fps in 1080P. ●AAC Audio Encoding Support AAC audio encoding, better sound quality and smaller bandwidth. ●Local Storage Support local storage module, directly recording to local USB flash disk without NVR. ●Low-light High SNR of CMOS sensor combined with 2D and 3D noise reduction algorithm, effectively reduce the noise, even under low illumination conditions, picture can still keep clean and clear. ●Abundant & Perfect Interface Support HDMI output, 3G-SDI interface, effective transmission distance up to 150 meters (under 1080p30). HDMI, SDI, Network can output at the same time. ●20x Optical + 16x Digital Zoom Use TAMRON high quality super telephoto lens, support 20x optical zoom, and 16x digital zoom (optional). ●Remote Control Using RS232/485 interface, all the parameters of the camera can be remote controlled by the high-speed communications.
----------------------	---

Model	VHD-V60CL-N
--------------	-------------

Name	HD Video Conference Camera
-------------	----------------------------

Camera	
---------------	--

Video System	HD: 1080p/60, 1080p/50, 1080i/60, 1080i/50, 1080p/30, 1080p/25, 720p/60(supported by network only), 720p/50, 720p/30, 720p/25 SD: 480i, 576i
Sensor	1/2.8", CMOS, Effective Pixel: 2.07M
Scanning Mode	Progressive
Lens	20x, f4.42mm ~ 88.5mm, F1.8 ~ F2.8
Digital Zoom	16x
Minimal	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K 1, 6500K 2, 6500K 3, One Push,
Backlight Compensation	Support
Digital Noise Reduction	2D&3D Digital Noise Reduction
Video S/N	≥55dB
Horizontal Angle of View	60.7° ~ 3.36°
Vertical Angle of View	34.1° ~ 1.89°
Horizontal Rotation Range	±170°
Vertical Rotation Range	-30° ~ +90°
Pan Speed Range	1.7° ~ 100°/s
Tilt Speed Range	1.7° ~ 69.9°/s
H & V Flip	Support
Image Freeze	Support
PoE	Support
Local Storage	Support
Number of Preset	255
Preset Accuracy	0.1°

IPC Features	
Video	H.264/MJPEG
Video Stream	Main Stream, Sub Stream
Main Stream Resolution	1920x1080, 1280x720, 1024x576
Sub Stream Resolution	1024x576, 720x480, 320x240
Video Bit Rate	32Kbps ~ 20480Kbps
Bit Rate Type	Variable Rate, Fixed Rate
Frame Rate	50Hz: 1fps ~ 25fps, 60Hz: 1fps ~ 30fps, 720p120: 120fps, 640x480p240: 240fps
Audio	AAC,G711A
Audio Bit Rate	96Kbps, 128Kbps, 256Kbps
Support protocols	NDI@ HX, NDI@ HX2,TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.
Input/Output Interface	
HD Output	1xHDMI: Verision 1.3
	1x3G-SDI: BNC type, 800mVp-p, 75Ω, Along to SMPTE 424M standard
SD Output	1xCVBS: 3.5mm mini jack, 1Vp-p, 75Ω
Network Interface	1xRJ45: 10M/100M Ethernet Interface
Audio Interface	1-ch: 3.5mm Audio Interface, Line In
USB	1xUSB2.0: Type A female jack
Communication Interface	1xRS232 In: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P
	1xRS232 Out: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA network use only
	1xRS485: 2pin Phoenix Port, Max Distance: 1200m, Protocol: VISCA/Pelco-D/Pelco-P
Power Jack	JEITA type (DC IN 12V)
Generic Specification	
Input Voltage	DC 12V / PoE (802.3af)
Current Consumption	1.0A (Max)
Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)
Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Power	12W (Max)
Size	146mm x 152mm x 164mm
Net Weight	1.35Kg (3.0lb)
Product Picture	